

ORFS-Pressarmatur Typ RPDUF / ORFS fitting type RPDUF					
Flachdichtkopf mit UNF-Überwurfmutter. / Flat sealing head with UNF union nut					
Art. Nr. Art. N°	Bezeichnung Description	Standard	DN	G1	S1
345.699	RPDUF 20 1"		20	1"	30
345.700	RPDUF 20 1.3/16"	•	20	1.3/16"	36
345.701	RPDUF 20 1.7/16"		20	1.7/16"	41
345.703	RPDUF 25 1.7/16"	•	25	1.7/16"	41
345.704	RPDUF 25 1.11/16"		25	1.11/16"	50
345.705	RPDUF 32 1.11/16"	•	32	1.11/16"	50
345.707	RPDUF 40 2"	•	40	2"	60



45° ORFS-Pressarmatur Typ RPKUF../4 / ORFS 45 ° fitting type RPKUF ../4					
Flachdichtkopf mit UNF-Überwurfmutter. / Flat sealing head with UNF union nut					
Art. Nr. Art. N°	Bezeichnung Description	Standard	DN	G1	S1
345.710	RPKUF 20 1.3/16"/4	•	20	1.3/16"	36
345.711	RPKUF 20 1.7/16"/4		20	1.7/16"	41
345.713	RPKUF 25 1.7/16"	•	25	1.7/16"	41
345.715	RPKUF 32 1.11/16"/4	•	32	1.11/16"	50
345.717	RPKUF 40 2"/4	•	40	2"	60



90° ORFS-Pressarmatur Typ RPKUF../9 / ORFS 90 ° fitting type RPKUF ../9					
Flachdichtkopf mit UNF-Überwurfmutter. / Flat sealing head with UNF union nut					
Art. Nr. Art. N°	Bezeichnung Description	Standard	DN	G1	S1
345.720	RPKUF 20 1.3/16"/9	•	20	1.3/16"	36
345.721	RPKUF 20 1.7/16"/9		20	1.7/16"	41
345.723	RPKUF 25 1.7/16"/9	•	25	1.7/16"	41
345.725	RPKUF 32 1.11/16"	•	32	1.11/16"	50
345.727	RPKUF 40 2"/9	•	40	2"	60



ORFS-Pressarmatur Typ RPAUF / ORFS fitting type RPAUF					
UNF-Aussengewinde, flachdichtend mit O-Ring (NBR). / UNF male thread, flat sealing with O-ring (NBR)					
Art. Nr. Art. N°	Bezeichnung Description	Standard	DN	G1	S1
345.730	RPAUF 20 1.3/16"	•	20	1.3/16"	32
345.733	RPAUF 25 1.7/16"	•	25	1.7/16"	38
345.735	RPAUF 32 1.11/16"	•	32	1.11/16"	46



Standard Standardgröße / Standard size
DN Durchmesser Nominal / Diameter nominal
G1 Gewinde / Thread
S1 Schlüsselweite / Hexagon