



<b>Kupplungsstecker BG5 Typ STF5...-S / Quick release coupling male type STF5...-S</b> Baugröße 5, flachdichtend. Betriebsdruck: max. 350 bar / Size 5, flat face				
Art. Nr. Art. N°	Bezeichnung Description	D1 (mm)	R1	G1
287.751	STF5-IG G1"-S	36	-	IG G1"
287.750	STF5-IG G1.1/4"-S	36	-	IG G1.1/4"
287.755	STF5-22L-S	36	L22	M30x2
287.756	STF5-28L-S	36	L28	M36x2
287.760	STF5-20S-S	36	S20	M30x2
287.761	STF5-25S-S	36	S25	M36x2
287.762	STF5-30S-S	36	S30	M42x2

<b>Kupplungsmuffe BG5 Typ STF5...-M / Quick release coupling female type STF5...-M</b> Baugröße 5, flachdichtend. Betriebsdruck: max. 350 bar / Size 5, flat face				
Art. Nr. Art. N°	Bezeichnung Description		R1	G1
287.701	STF5-IG G1"-M		-	IG G1"
287.700	STF5-IG G1.1/4"-M		-	IG G1.1/4"
287.705	STF5-22L-M		L22	M30x2
287.706	STF5-28L-M		L28	M36x2
287.710	STF5-20S-M		S20	M30x2
287.711	STF5-25S-M		S25	M36x2
287.712	STF5-30S-M		S30	M42x2

<b>Kupplungsstecker BG5 Typ STFS5...-S / Quick release coupling male type STFS5...-S</b> Schottausführung, flachdichtend, Baugröße 5. Betriebsdruck: max. 350 bar / Bulkhead, flat face, size 5				
Art. Nr. Art. N°	Bezeichnung Description	D1 (mm)	R1	G1
287.765	STFS5-22L-S	36	L22	M30x2
287.766	STFS5-28L-S	36	L28	M36x2
287.770	STFS5-20S-S	36	S20	M30x2
287.771	STFS5-25S-S	36	S25	M36x2
287.772	STFS5-30S-S	36	S30	M42x2

<b>Kupplungsmuffe BG5 Typ STFS5...-M / Quick release coupling female type STFS5...-M</b> Schottausführung, flachdichtend, Baugröße 5. Betriebsdruck: max. 350 bar / Bulkhead, flat face, size 5				
Art. Nr. Art. N°	Bezeichnung Description		R1	G1
287.715	STFS5-22L-M		L22	M30x2
287.716	STFS5-28L-M		L28	M36x2
287.720	STFS5-20S-M		S20	M30x2
287.721	STFS5-25S-M		S25	M36x2
287.722	STFS5-30S-M		S30	M42x2

**D1 (mm)** Durchmesser / Diameter  
**R1** Rohrgröße / Pipe size  
**G1** Gewinde / Thread

