



Steckkupplungs-Stecker BG1 Typ ST1...-S / Quick release coupling male type ST1...-S
Baugröße 1. Betriebsdruck: max. 350 bar / Size 1

Art. Nr. Art. N°	Bezeichnung Description	D1 (mm)	R1	G1
288.110	ST1-IG G1/8"-S	12	-	IG G1/8"
288.111	ST1-IG G1/4"-S	12	-	IG G1/4"
288.120	ST1-06L-S	12	L06	M12x1,5
288.121	ST1-08L-S	12	L08	M14x1,5
288.122	ST1-10L-S	12	L10	M16x1,5
288.130	ST1-06S-S	12	S06	M14x1,5
288.131	ST1-08S-S	12	S08	M16x1,5
288.132	ST1-10S-S	12	S10	M18x1,5

Steckkupplungs-Muffe BG1 Typ ST1...-M / Quick release coupling female type ST1...-M
Baugröße 1. Betriebsdruck: max. 350 bar / Size 1

Art. Nr. Art. N°	Bezeichnung Description	R1	G1
288.010	ST1-IG G1/8"-M	-	IG G1/8"
288.011	ST1-IG G1/4"-M	-	IG G1/4"
288.020	ST1-06L-M	L06	M12x1,5
288.021	ST1-08L-M	L08	M14x1,5
288.022	ST1-10L-M	L10	M16x1,5
288.030	ST1-06S-M	S06	M14x1,5
288.031	ST1-08S-M	S08	M16x1,5
288.032	ST1-10S-M	S10	M18x1,5



Schottadapter / Einschraubstutzen
Bulkhead adapter / male stud coupling
Seite / page 139 - 141

D1 (mm) Durchmesser / Diameter
R1 Rohrgröße / Pipe size
G1 Gewinde / Thread