



DKJ - Schraubarmatur Typ IDU / DKJ - Screw fitting type IDU						
JIC-Dichtkopf (74°-Innenkonus) mit UNF-Überwurfmutter JIC sealing cone (74° inside cone) with UNF union nut						
Art. Nr. Art. N°	Bezeichnung Description	Standard	DN	G1	S1	S2
236.000	IDU 06 7/16"	•	06	7/16"	15	14
236.001	IDU 06 1/2"		06	1/2"	17	17
236.002	IDU 06 9/16"		06	9/16"	19	17
236.005	IDU 08 9/16"		08	9/16"	19	19
236.010	IDU 10 9/16"	•	10	9/16"	19	19
236.011	IDU 10 3/4"		10	3/4"	24	22
236.015	IDU 12 3/4"	•	12	3/4"	24	24
236.016	IDU 12 7/8"		12	7/8"	27	27
236.020	IDU 16 7/8"	•	16	7/8"	27	27
236.021	IDU 16 1.1/16"		16	1.1/16"	32	30
236.025	IDU 20 1.1/16" *	•	20	1.1/16"	32	32
236.030	IDU 25 1.5/16" *	•	25	1.5/16"	38	38



45° DKJ - Schraubarmatur Typ IKU ../4 / 45°DKJ - screw fitting type IKU ../4						
JIC-Dichtkopf (74°-Innenkonus) mit UNF-Überwurfmutter JIC sealing cone (74° inside cone) with UNF union nut						
Art. Nr. Art. N°	Bezeichnung Description	Standard	DN	G1	S1	S2
236.050	IKU 06 7/16"/4	•	06	7/16"	15	14
236.051	IKU 06 1/2"/4		06	1/2"	17	14
236.052	IKU 06 9/16"/4		06	9/16"	19	14
236.055	IKU 08 9/16"/4		08	9/16"	19	14
236.060	IKU 10 3/4"/4		10	3/4"	24	17
236.065	IKU 12 7/8"/4		12	7/8"	27	20
236.075	IKU 20 1.1/16"/4 *	•	20	1.1/16"	32	27
236.080	IKU 25 1.5/16"/4 *	•	25	1.5/16"	38	32

* Armaturen DN20 / DN25 auf Anfrage
* Fittings DN20 / DN25 on request

90° DKJ - Schraubarmatur Typ IKU ../9 / 90° DKJ - Screw fitting type IKU ../9						
JIC-Dichtkopf (74°-Innenkonus) mit UNF-Überwurfmutter JIC sealing cone (74° inside cone) with UNF union nut						
Art. Nr. Art. N°	Bezeichnung Description	Standard	DN	G1	S1	S2
236.100	IKU 06 7/16"/9	•	06	7/16"	15	14
236.101	IKU 06 1/2"/9		06	1/2"	17	14
236.102	IKU 06 9/16"/9		06	9/16"	19	14
236.105	IKU 08 9/16"/9		08	9/16"	19	14
236.110	IKU 10 9/16"/9	•	10	9/16"	19	17
236.111	IKU 10 3/4"/9		10	3/4"	24	17
236.115	IKU 12 3/4"/9	•	12	3/4"	24	20
236.116	IKU 12 7/8"/9		12	7/8"	27	20
236.120	IKU 16 1.1/16"/9		16	1.1/16"	32	24
236.125	IKU 20 1.1/16"/9 *	•	20	1.1/16"	32	27
236.130	IKU 25 1.5/16"/9 *	•	25	1.5/16"	38	32



AGJ - Schraubarmatur Typ IAU / AGJ - Screw fitting type IAU					
JIC-Aussengewinde (74°-Aussenkonus) JIC male thread (74° outside cone)					
Art. Nr. Art. N°	Bezeichnung Description	Standard	DN	G1	S1
236.150	IAU 06 1/2"		06	1/2"	14
236.155	IAU 08 9/16"		08	9/16"	17
236.160	IAU 10 3/4"		10	3/4"	19



Standard Standardgröße / Standard size
DN Durchmesser Nominal / Diameter nominal
G1 Gewinde / Thread
S1 Schlüsselweite / Hexagon
S2 Schlüsselweite / Hexagon

* Armaturen DN20 / DN25 auf Anfrage
 * Fittings DN20 / DN25 on request